



basic education

Department:
Basic Education
REPUBLIC OF SOUTH AFRICA

NATIONAL SENIOR CERTIFICATE

GRADE 12

INFORMATION TECHNOLOGY P1

FEBRUARY/MARCH 2013

MEMORANDUM

MARKS: 120

This memorandum consists of 29 pages.

GENERAL INFORMATION

- These marking guidelines are to be used as the basis for the marking session. They were prepared for use by markers, all of whom are required to attend a rigorous standardisation meeting to ensure that the guidelines are consistently interpreted and applied in the marking of candidates' scripts.
- It is acknowledged that there may be different views about some matters of emphasis or detail in the guidelines, and different interpretations of the application thereof.
- Note that learners who provide an alternate correct solution to that given in the marking guidelines will be given full credit for the relevant question.
- **ANNEXURES A, B and C** (pages 3–6) include the marking grid for each question for using either one of the two programming languages.
- **ANNEXURES D, E and F** (pages 7–16) contain the solutions for Delphi for QUESTIONS 1 to 3 in programming code.
- **ANNEXURES G, H, I and J** (pages 17–29) contain the solutions for Java for QUESTIONS 1 to 3 in programming code.
- Copies of ANNEXURES A, B and C (pages 3–6) should be made for each learner and completed during the marking session.

ANNEXURE A

QUESTION 1: MARKING GRID – PROGRAMMING AND DATABASE

CENTRE NUMBER:		EXAMINATION NUMBER:	
QUESTION	DESCRIPTION	MAX. MARKS	LEARNER'S MARKS
1.1	Query: Correct fields (or *) ✓; correct table ✓; ORDER BY correct fields in correct order ✓ Desc ✓	4	
	SQL: SELECT * FROM tblTours ORDER BY Destination, StartDate Desc		
1.2	Query: Correct field & table ✓; FirstName starting with C ✓; surname starting with C ✓; displaying correct gender ✓	4	
	SQL(D): SELECT TourID, FirstName, Surname FROM tblTourists WHERE FirstName LIKE "C%" AND Surname LIKE "C%" AND Gender = "F"		
	SQL (J): SELECT TourID, FirstName, Surname FROM tblTourists WHERE FirstName LIKE 'C%' AND Surname LIKE 'C%' AND Gender = 'F'		
1.3	Query: Correct fields & table ✓; correct WHERE clause displaying if Deposit is paid ✓ and build input (sX) into SQL string with LIKE ✓ starting with sX ✓	4	
	SQL (D): 'SELECT TourID, Surname FROM tblTourists WHERE (Deposit) AND (Country LIKE "" + sX + "%")'		
	SQL (J): "SELECT TourID, Surname FROM tblTourists WHERE (Deposit) AND (Country LIKE "" + sX + "%") "		
1.4	Query: Correct fields & table ✓; NumberOfDays field correctly calculated and displayed ✓✓; Correct WHERE clause using start date (#2012/06/12#) ✓ and end date (#2012/10/13#) ✓; must be away for more than 5 days ✓	6	
	SQL: SELECT Surname, StartDate, (EndDate-StartDate) +1 AS NumberOfDays FROM tblTours WHERE (StartDate >= #2012/06/12#) AND (StartDate <= #2012/10/31#) AND ((EndDate-StartDate) + 1 > 5)		
1.5	Query: DELETE FROM correct table ✓; WHERE EndDate ✓ testing for Year ✓; against correct year ✓	4	
	SQL: DELETE FROM tblTours WHERE YEAR(EndDate) = 2011		
	NOTE: May not use StartDate		
	Alternative: SQL(D) DELETE FROM tblTours WHERE EndDate LIKE "%2011%"		
	Alternative: SQL(J) DELETE FROM tblTours WHERE EndDate LIKE '%2011%'		

QUESTION 1: MARKING GRID – PROGRAMMING AND DATABASE – continue

1.6	Query: Correct fields & table ✓; SUM on correct field ✓ format result as Currency ✓ AS IncomePerCountry ✓ GROUP BY on Country field ✓ SQL(D): SELECT Country, Format(SUM(AmountPaid), "Currency") AS IncomePerCountry FROM tblTourists GROUP BY Country SQL(J): SELECT Country, Format(SUM(AmountPaid), 'Currency') AS IncomePerCountry FROM tblTourists GROUP BY Country	5	
1.7	Query: Correct fields from both tables ✓ including the calculated field ✓; correct WHERE clause linking tables with TourID ✓; correct GROUP BY clause (note order of fields) ✓; correct HAVING clause ✓ count number of tourist ✓ less than seats available ✓ SQL: Using aliases for table names: SELECT T.Destination, T.StartDate, T.Seats, Count(V.Surname) AS [SeatsBooked] FROM tblTours T, tblTourists V WHERE T.TourID = V.TourID GROUP BY Destination, StartDate, Seats HAVING Count(V.Surname) < T.Seats Alternative: SELECT Destination, StartDate, tblTours.Seats, Count(tblTourists.Surname) AS [SeatsBooked] FROM tblTours, tblTourists WHERE tblTourists.TourID = tblTours.TourID GROUP BY Destination, StartDate, Seats HAVING Count(tblTourists.Tourist) < tblTours.Seats	7	
	TOTAL:	34	

ANNEXURE B**QUESTION 2: MARKING GRID – OBJECT-ORIENTED PROGRAMMING**

CENTRE NUMBER:		EXAMINATION NUMBER:	
QUESTION	DESCRIPTION	MAX. MARKS	LEARNER'S MARKS
2.1.1	setTariff METHOD: Test for Apr OR✓ Sept OR Dec all three months✓ Assign 1250✓ to tariff attribute✓ Repeat for Jan, Feb, Aug, Oct, Nov ; Assign 1000✓ Repeat for March, May, June, July ; Assign 900✓	6	
2.1.2	PARAMETERISED CONSTRUCTOR: Correct order and data type of parameters✓✓; Assign five parameters✓; call set method for tariff per day✓	4	
2.1.3	shortenString METHOD: First character of month✓; Loop✓ from second char✓ build result string✓ if character not a vowel ✓	5	
2.1.4	findLuckyChar METHOD: Loop until not a space ✓; random number ✓✓ based on length of destination ✓ result ✓	5	
2.1.5	toString METHOD: Use shortenString method ✓; <eoln or #13> character ✓ Labels ✓ display numerical data correct ✓ other attributes display correctly ✓	5	
2.2.1	Declares object array size 50✓ and array counter ✓	2	
2.2.2	INITIALISATION OF ARRAY: Test if file exist ✓ <i>File doesn't exists:</i> Display message and terminate/exit program/event✓ <i>File does exists:</i> {Delphi: AssignFile, Reset and CloseFile Java: Create object to read from file} ✓; Init array counter and change array counter ✓; Loop through file ✓; Read two lines from text file✓ ; Separate first line using (&)✓; Separate second line using (" for ")✓ and (" days#") ✓ Instantiate object using parameterized constructor ✓✓✓	12	
2.2.3	MENU OPTION A: Input month ✓; display headings ✓; Loop through array ✓ IF month ✓; Display info (counter correct) ✓	5	
	Prompt and input tour no ✓ Display tour information using toString() method ✓	2	
	Prompt for character and display destination ✓ Input guess char✓; use findLuckyChar method ✓ IF guess char = lucky char ✓ THEN: calculate discount ✓ and display ✓ ELSE: display lucky character and message ✓ Both messages must display original price ✓	8	
	TOTAL:	54	

ANNEXURE C**QUESTION 3: MARKING GRID - PROBLEM-SOLVING PROGRAMMING**

CENTRE NUMBER:		EXAMINATION NUMBER:	
QUESTION	DESCRIPTION	MAX. MARKS	LEARNER'S MARKS
3.1	MENU OPTION A: Init Total ✓; Loop through array ✓ IF Country = France OR Germany OR Spain ✓✓ Extract the number of euro's and add to total ✓✓ Calculate rand value ✓ Display both values with formatting ✓	8	
3.2	MENU OPTION B: Loop though array ✓ IF Robben Island tour ✓✓ Find index of #RO# ✓ IF tourist from ENGLAND OR ✓ CANADA ✓ Replace #RO# ✓ with #ROEnglish# ✓ Display name of tourist ✓✓ ELSE: Replace #RO# with #ROOther# ✓	11	
3.3	MENU OPTION C: Step with loop through destination array ✓ initialise visit counter ✓ copy destination code ✓ Step with loop through tourist array ✓ determine IF tourist is visiting destination ✓✓ increase visit count ✓ calculate number of stars ✓ build output string: destination ✓ and Step with loop to add number of stars ✓✓ and (number of visits) ✓ Display string ✓	13	
TOTAL:		32	

SUMMARY OF LEARNER'S MARKS:

	QUESTION 1	QUESTION 2	QUESTION 3	GRAND TOTAL
MAX. MARKS	34	54	32	120
LEARNER'S MARKS				

ANNEXURE D: SOLUTION – QUESTION 1: DELPHI

```

unit Question1U_MEMO;
  //Solution for Question 1
interface

uses
  Windows, Messages, SysUtils, Variants, Classes, Graphics, Controls, Forms,
  Dialogs, StdCtrls, DB, ADODB, Grids, DBGrids, ExtCtrls, Buttons, Menus;

type
  TfrmRec = class(TForm)
    qryRec: TADOQuery;
    dsrQry: TDataSource;
    grdRec: TDBGrid;
    mnuMain: TMainMenu;
    mnuOptionA: TMenuItem;
    mnuOptionB: TMenuItem;
    mnuOptionC: TMenuItem;
    mnuOptionD: TMenuItem;
    mnuOptionE: TMenuItem;
    mnuOptionF: TMenuItem;
    mnuOptionG: TMenuItem;
    mnuQuit: TMenuItem;
    procedure mnuOptionAClick(Sender: TObject);
    procedure mnuOptionBClick(Sender: TObject);
    procedure mnuOptionCClick(Sender: TObject);
    procedure mnuOptionDClick(Sender: TObject);
    procedure mnuOptionEClick(Sender: TObject);
    procedure mnuOptionFClick(Sender: TObject);
    procedure mnuOptionGClick(Sender: TObject);
    procedure mnuQuitClick(Sender: TObject);
  private
    { Private declarations }
  public
    { Public declarations }
  end;

var
  frmRec: TfrmRec;

implementation

{$R *.dfm}
//=====
procedure TfrmRec.mnuOptionAClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT * FROM tblTours ORDER BY Destination, StartDate
Desc';
  qryRec.Open;
end;
//=====
procedure TfrmRec.mnuOptionBClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT TourID, FirstName, Surname ' +
'FROM tblTourists ' +
'WHERE Surname LIKE "C%" AND FirstName LIKE "C%" AND ' +
'Gender = "F"';
  qryRec.Open;
end;
//=====

```

```

procedure TfrmRec.mnuOptionCClick(Sender: TObject);
var
  sX : String;
begin
  sX := InputBox('Question 1', 'Country of origin?', 'Spain');
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT TourID, Surname FROM tblTourists ' +
    'WHERE (Deposit = TRUE) AND ' +
    '(Country = "' + sX + '")';

  qryRec.Open;
end;
//=====
procedure TfrmRec.mnuOptionDClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT Surname, StartDate, EndDate, ' +
    '(EndDate-StartDate)+1 AS NumberOfDays ' +
    'FROM tblTours ' +
    'WHERE (Startdate >= #2012/06/12#) AND ' +
    '(StartDate <= #2012/10/31#) AND ' +
    '((EndDate-StartDate) + 1 > 5) ';

  qryRec.Open;
end;
//=====
procedure TfrmRec.mnuOptionEClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'DELETE FROM tblTours WHERE Year(EndDate) = 2011';
  qryRec.ExecSQL;
  MessageDlg('Records Processed Successfully',mtInformation,[mbOk],0);
end;

procedure TfrmRec.mnuOptionFClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT Country, ' +
    'Format(Sum(AmountPaid),"Currency")AS IncomePerCountry' +
    'FROM tblTourists ' +
    'GROUP BY Country';

  qryRec.Open;
end;
//=====
procedure TfrmRec.mnuOptionGClick(Sender: TObject);
begin
  qryRec.Close;
  qryRec.SQL.Text := 'SELECT T.Destination, T.StartDate, T.Seats, ' +
    'Count(V.Surname) AS [SeatsBooked]' +
    'FROM tblTours T, tblTourists V ' +
    'WHERE T.TourID = V.TourID ' +
    'GROUP BY Destination, StartDate, Seats ' +
    'HAVING Count(V.Surname) < T.Seats';

  qryRec.Open;
end;
//=====

procedure TfrmRec.mnuQuitClick(Sender: TObject);
begin
  Application.Terminate;
end;

end.

```


ANNEXURE E: SOLUTION – QUESTION 2: DELPHI**CLASS UNIT:**

```

unit uQuest2_MEMO;
//solution for Question 2 - class
interface

TYPE
  TData = class(TObject)
  private
    FGName      : String;
    FDName      : String;
    FMName      : String;
    FNumD       : Integer;
    FNumT       : Integer;
    FTariff     : Real;
  public
    function getGName : String;
    function getDName : String;
    function getMName : String;
    function getNumD  : Integer;
    function getNumT  : Integer;
    function getTariff: Real;

    constructor Create(sGuide, sDestination, sMonth: String; iDays, iNum :
Integer);
    procedure setTariff;
    function shortenString : String;
    function findLuckyChar : Char;
    function toString : String;
  end;

implementation

uses SysUtils;

{ TData }
//=====
constructor TData.Create(sGuide, sDestination, sMonth: String; iDays, iNum:
Integer);
begin
  FGName      := sGuide;
  FDName      := sDestination;
  FMName      := sMonth;
  FNumD       := iDays;
  FNumT       := iNum;
  setTariff;
end;
//=====
procedure TData.setTariff;
var
  sMonth : String;
begin
  sMonth := Uppercase(FMName);
  //accept solution without the use of uppercase.
  IF (sMonth = 'APRIL') OR (sMonth = 'SEPTEMBER') OR (sMonth = 'DECEMBER')
  then
    FTariff := 1250.00
  else
    IF (sMonth = 'MARCH') OR (sMonth = 'MAY') OR (sMonth = 'JUNE') OR (sMonth
= 'JULY')
    then

```

```

    fTariff := 900.00
  else
    fTariff := 1000.00;
end;
//=====
function TData.shortenString: String;
var
  a : Integer;
  sTemp : String;
begin
  sTemp := fMName[1];
  for a := 2 to length(fMName) do
    if NOT(Uppcase(fMName[a]) in ['A','E','I','O','U'])
      then sTemp := sTemp + fMName[a];
    Result := sTemp;
    //accept solution without upcase where small letters are added to set
  end;
//=====
function TData.findLuckyChar: Char;
var
  iMax, iLuckyNum : Integer;
begin
  iMax := length(fDName);
  Repeat
    iLuckyNum := random(iMax)+1;
  Until fDName[iLuckyNum] <> #32;

  Result := fDName[iLuckyNum];
end;
//=====
function TData.toString: String;
begin
  Result := 'Month: ' + shortenString + #13 +
    'Destination: ' + fDName + ' with ' + fGName + ' as the tour
guide' + #13 +
    'Price: ' + FloatToStrF(fTariff, ffCurrency, 9,2) + ' per day for
a period of '+ IntToStr(fNumD) + ' days' +
#13+InttoStr(fNumT) + ' tourists are taking this tour.';
end;
//=====
function TData.getGName: String;
begin
  Result := fGName;
end;

function TData.getDName: String;
begin
  Result := fDName;
end;

function TData.getMName: String;
begin
  Result := fMName;
end;

function TData.getNumD: Integer;
begin
  Result := fNumD;
end;

function TData.getNumT: Integer;
begin
  Result := fNumT;
end;

```

```
function TData.getTariff: Real;
begin
  Result := fTariff;
end;

end.
```

FORM UNIT:

```
unit Question2U_MEMO;
interface

uses
  Windows, Messages, SysUtils, Variants, Classes, Graphics, Controls, Forms,
  Dialogs, StdCtrls, ComCtrls, Menus,
  uQuest2_MEMO;
type
  TfrmQ2 = class(TForm)
    mnuMain: TMainMenu;
    mnuOptionA: TMenuItem;
    mnuQuit: TMenuItem;
    redQ2: TRichEdit;
    procedure mnuQuitClick(Sender: TObject);
    procedure mnuOptionAClick(Sender: TObject);
    procedure FormCreate(Sender: TObject);
  private
    { Private declarations }
  public
    { Public declarations }
  end;

var
  frmQ2: TfrmQ2;

  arrTours : Array[1..50] of TData;
  iCount   : Integer = 0;

implementation

{$R *.dfm}
{$R+}
//=====
procedure TfrmQ2.FormCreate(Sender: TObject);
var
  TF          : TextFile;
  sLineA, sLineB : String;
  sGName, sDName, sMnth, sDays, sNumT : String;
begin
  {Code for onCreate event of form}
  randomize;
  IF NOT FileExists('DataQ2.txt')
  then
    begin
      begin
        MessageDlg('ERROR: File not found.', mtError, [mbOk], 0);
        mnuOptionA.Enabled := False;
        Exit;
      end;
    end;

  AssignFile(TF, 'DataQ2.txt');
  Reset(TF);
```

```

While NOT EOF(TF) DO
  Begin
    Readln(TF, sLineA);
    Readln(TF, sLineB);

    sGName := copy(sLineA, 1, pos('&', sLineA)-1);
    sDName := copy(sLineA, pos('&', sLineA)+1, length(sLineA));

    sMnth := copy(sLineB, 1, pos(' for ', sLineB) -1);
    Delete(sLineB, 1, pos('for', sLineB)+3); //delete space after for also
    sDays := copy(sLineB, 1, pos(' ', sLineB)-1);
    Delete(sLineB, 1, pos('#', sLineB));
    sNumT := sLineB;

    Inc(iCount, 1);
    arrTours[iCount] := TData.Create(sGName, sDName, sMnth, StrToInt(sDays),
StrToInt(sNumT));
    End; //while
  CloseFile(TF);
end;
//=====
procedure TfrmQ2.mnuOptionAClick(Sender: TObject);
var
  sMnth, sLucy          : String;
  a, iTNum             : Integer;
  rNTariff             : Real;
  cLChar               : Char;
begin
  {Code Option A}
  sMnth := InputBox('Question 2', 'Enter the month of tour (e.g. February)?',
  '');
  redQ2.Lines.Clear;
  redQ2.Paragraph.TabCount := 1;
  redQ2.Paragraph.Tab[0] := 100;
  redQ2.Lines.Add('Tours for the month of ' + sMnth);
  redQ2.Lines.Add('=====');
  redQ2.Lines.Add('Number' + #9 + 'Destination');
  for a := 1 to iCount do
    begin
      if Uppercase(arrTours[a].getMName) = Uppercase(sMnth)
      then redQ2.Lines.Add(intToStr(a) + #9 + arrTours[a].getDName);
    end;

    iTNum := StrToInt(InputBox('Question 2', 'Enter the number of a tour from the
list', '35'));
    redQ2.Lines.Add('');
    redQ2.Lines.Add(arrTours[iTNum].toString);

    redQ2.Lines.Add(' ');
    sLucy := InputBox('Question 2', 'Enter any character from ' +
      arrTours[iTNum].getDName + ' .', 'a');
    cLChar := arrTours[iTNum].findLuckyChar;
    IF Upcase(cLChar) = UpCase(sLucy[1])
    then
      begin
        rNTariff := arrTours[iTNum].getTariff * 0.75; //25% discount
        redQ2.Lines.Add('Congratulations! You have received 25% discount '+
          'on the daily tariff!' + #13 +
          'The tariff was ' +
          FloatToStrF(arrTours[iTNum].getTariff, ffCurrency, 8,2) +
          ' per day. It has been reduced to ' +
          FloattoStrF(rNTariff, ffCurrency, 8, 2) + ' per day');
      end
    end
  end

```

```
else
  begin
    redQ2.Lines.Add('The lucky character was the letter '+ cLChar + '.'+#13 +
      'No discount. The tariff is still ' +
      FloatToStrF(arrTours[itNum].getTariff, ffCurrency, 8,2) + ' per
day');
    end;
end;
//=====
procedure TfrmQ2.mnuQuitClick(Sender: TObject);
begin
  Application.Terminate;
end;

end.
```

ANNEXURE F: SOLUTION – QUESTION 3: DELPHI

```

unit Question3U_MEMO;
interface

uses
  Windows, Messages, SysUtils, Variants, Classes, Graphics, Controls, Forms,
  Dialogs, StdCtrls, ComCtrls, Menus;

type
  TfrmQ3 = class(TForm)
    mnuMain: TMainMenu;
    mnuOptionA: TMenuItem;
    mnuOptionB: TMenuItem;
    mnuQuit: TMenuItem;
    redQ3: TRichEdit;
    mnuOptionC: TMenuItem;
    procedure mnuQuitClick(Sender: TObject);
    procedure mnuOptionAClick(Sender: TObject);
    procedure mnuOptionBClick(Sender: TObject);
    procedure mnuOptionCClick(Sender: TObject);
  private
    { Private declarations }
  public
    { Public declarations }
  end;

var
  frmQ3: TfrmQ3;

  arrData : Array[1..40] of String =
    ('Rachel Delarosa@Canada#SH#11861', 'Corradino Grande@Spain#RO#5788',
    'Lucas Herder@Germany#KR#7709', 'Estotz Lizarazu@France#GA#12349',
    'Chynna Taylor@England#GA#8551', 'Renata Di@Spain#RO#4906',
    'Ugs Boulot-Tolle@France#CA#7300', 'Lena Bucholtz@Germany#GA#10344',
    'Maria Heimpel@Germany#SH#9438', 'Julian Amstadter@Germany#RO#8840',
    'Sofie Mosbauer@Germany#GA#5894', 'Fiona Green@England#CA#9094',
    'Sara Escobedo@Canada#KR#4381', 'Nataly Mahan@Canada#RO#12642',
    'Wyatt Parham@Canada#SH#4799', 'Noah Donovan@Canada#SH#3888',
    'Joseph Scott@England#SH#7928', 'Emily Smith@England#KR#3110',
    'Adriana Mancuso@Spain#RO#3724', 'Cassandra Wilder@Canada#KR#12583',
    'Tomasino Camporese@Spain#KR#6777', 'Stacy Anderson@England#RO#3686',
    'Guiraud Bluteau@France#RO#11592', 'Damian Friedman@Canada#RO#9012',
    'Anne Loef@Germany#KR#13035', 'Terence Brown@England#SH#8180',
    'Lion Ghislieri@Spain#RO#14343', 'Giraudetz Girardin@France#CA#11644',
    'Guglielmo Capriati@Spain#SH#5408', 'David Geiberger@Germany#RO#9854',
    'Irisa Cooper@England#KR#11456', 'Hayden Mcdonough@Canada#KR#7840',
    'Jonas Hipp@Germany#RO#3137', 'Emily Kohler@Germany#GA#6509',
    'Emily Thul@Germany#RO#8551', 'Gino Lazzaretti@Spain#CA#2329',
    'Alex Hofstater@Germany#GA#6751', 'Peers Scott@England#RO#9470',
    'Liliana Horne@Canada#RO#14689', 'Leon Kleinpaul@Germany#RO#15194');
implementation

VAR
  //array used for Option 3.
  arrDest : array[1..6] of string =
    ('Cape Winelands', 'Garden Route', 'Kruger National Park',
    'Robben Island (English tour)', 'Robben Island (Other tour)',
    'Shakaland');

{$R *.dfm}

```

```

{$R+}
//=====
procedure TfrmQ3.mnuOptionAClick(Sender: TObject);
var
    a          : Integer;
    rRand, rTotal : Real;
    sTemp      : String;
begin
    {Code Option A}
    redQ3.Lines.Clear;
    rTotal := 0;
    for A := 1 to 40 do
        begin
            IF ((pos('France', arrData[a]) > 0) OR (pos('Germany', arrData[a]) > 0)
                OR (pos('Spain', arrData[a]) > 0))
            then
                begin
                    sTemp := arrData[a];
                    Delete(sTemp, 1, pos('#', sTemp));
                    Delete(sTemp, 1, pos('#', sTemp));
                    rTotal := rTotal + StrToFloat(sTemp);
                end;
            end;
            rRand := rTotal * 10.75;
            redQ3.Lines.Add('Total amount in euro: ' + FloatToStr(rTotal));
            redQ3.Lines.Add('Total amount in South African rand: ' +
                FloatToStrF(rRand, ffCurrency, 8, 2));
        end;
    end;
//=====
procedure TfrmQ3.mnuOptionBClick(Sender: TObject);
var
    a, Index : Integer;
begin
    {Code Option B}
    redQ3.Lines.Clear;
    redQ3.Lines.Add('List of English-speaking tourists to Robben Island:');
    redQ3.Lines.Add('=====');
    for a := 1 to 40 do
        begin
            if pos('#RO#', arrData[a]) > 0
            then
                begin
                    Index := pos('#RO#', arrData[a]);
                    IF (pos('Canada', arrData[a]) > 0) OR
                        (pos('England', arrData[a]) > 0)
                    then
                        begin
                            Delete(arrData[a], Index, 4);
                            Insert('#ROEnglish#', arrData[a], Index);
                            //Insert('English', arrData[a], Index+4); //alternative
                            redQ3.Lines.Add(Copy(arrData[a], 1, pos('@', arrData[a])-1));
                        end //Canada & England
                    else
                        begin
                            Delete(arrData[a], Index, 4);
                            Insert('#ROOther#', arrData[a], Index);
                            //Insert('Other', arrData[a], Index+4); //alternative
                        end;
                    end; //Robben Island
                end;
        end;
    end;
//=====

```

```

procedure TfrmQ3.mnuOptionCClick(Sender: TObject);

var
  arrCount :array[1..6] of integer;
  a, b,iRating :integer;
  sDest :string;
  sRating      :string;
begin
  redQ3.Lines.Clear;
  redQ3.Paragraph.TabCount := 2;
  redQ3.Paragraph.Tab[0]   := 150;
  redQ3.Paragraph.Tab[1]   := 200;
  redQ3.Lines.Add('Star rating of tours');
  redQ3.Lines.Add('=====');
  redQ3.Lines.Add('Destination' + #9 + 'Rating' + #9 + 'Number of tourists');
  redQ3.Lines.Add('=====');
  for a := 1 to 6 do
    arrCount[a] := 0;

  for a := 1 to 40 do
    begin
      sDest := Uppercase(copy(arrData[a], pos('#',arrData[a])+1,3));
      case sDest[1] of
        'C' : inc(arrCount[1],1);//Cape Winelands
        'G' : inc(arrCount[2],1);//Garden Route
        'K' : inc(arrCount[3],1);//Kruger National Park
        'R' : case sDest[3] of //Robben Island
          'E' : inc(arrCount[4],1);//English
          'O' : inc(arrCount[5],1);//Other
        end;
        'S' : inc(arrCount[6],1);//Shakaland
      end;
    end;//for
  // Output
  For a := 1 to 6 do
    begin
      sRating := '';
      iRating := arrCount[a] div 3;
      for b := 1 to iRating do
        sRating := sRating + '*';
      redQ3.Lines.Add(arrDest[a] + #9 + sRating + #9 + '(' +
        IntToStr(arrCount[a]) + ')');
    end;//
  end;
  //=====
procedure TfrmQ3.mnuQuitClick(Sender: TObject);
begin
  Application.Terminate;
end;

end.

```


ANNEXURE G: SOLUTION – QUESTION 1: JAVA

```

import java.io.BufferedReader;
import java.io.InputStreamReader;
import java.io.IOException;
import java.sql.*;

public class TestQuestion1_MEMO
{
    public static void main (String[] args) throws SQLException,IOException
    {

        BufferedReader inKb = new BufferedReader (new InputStreamReader
(System.in));

        Tourism DB = new Tourism();
        System.out.println();

        char choice = ' ';
        do
        {
            System.out.println("\n\n      MENU");
            System.out.println();
            System.out.println("      Option A");
            System.out.println("      Option B");
            System.out.println("      Option C");
            System.out.println("      Option D");
            System.out.println("      Option E");
            System.out.println("      Option F");
            System.out.println("      Option G");
            System.out.println();
            System.out.println("      Q - QUIT");
            System.out.println(" ");
            System.out.print("      Your choice? ");
            choice = inKb.readLine().toUpperCase().charAt(0);
            System.out.println(" ");
            String sql = "";
            switch(choice)
            {
                case 'A': // Question 1.1
                {
                    sql = "SELECT * FROM tblTours ORDER BY Destination, StartDate
Desc";
                    DB.query(sql);
                    break;
                }
                //=====
                case 'B': // Question 1.2
                {
                    sql = "SELECT TourID, FirstName, Surname FROM tblTourists
WHERE FirstName LIKE 'C%'AND Surname LIKE 'C%' AND Gender = 'F'";
                    DB.query(sql);
                    break;
                }
                //=====
                case 'C': // Question 1.3
                {
                    System.out.println("Option C\nCountry of origin (e.g. Spain)?
");
                    String sX = inKb.readLine();
                    sql = "SELECT TourID, Surname FROM tblTourists WHERE Deposit
AND Country LIKE '" + sX + "%'";
                    DB.query(sql);

```

```
        break;
    }
//=====
    case 'D':    // Question 1.4
    {
        sql = "SELECT Surname, StartDate, EndDate, (Enddate-
StartDate)+1 AS NumberOfDays FROM tblTours WHERE (Startdate >= #2012/06/12#)
AND (StartDate <= #2012/10/31#) AND (endDate-StartDate + 1 > 5)";
        DB.query(sql);
        break;
    }
//=====
    case 'E':    // Question 1.5
    {
        sql = "DELETE FROM tblTours WHERE YEAR(EndDate) = 2011";
        DB.query(sql);
        break;
    }
//=====
    case 'F':    // Question 1.6
    {
        sql = "SELECT Country, Format(SUM(AmountPaid),'Currency') AS
IncomePerCountry FROM tblTourists GROUP BY Country";
        DB.query(sql);
        break;
    }
//=====
    case 'G':    // Question 1.7
    {
        sql = "SELECT Destination, StartDate, Seats,
Count(tblTourists.Surname) AS [SeatsBooked] FROM tblTours, tblTourists WHERE
tblTourists.TourID = tblTours.TourID GROUP BY Destination, StartDate, Seats
HAVING Count(tblTourists.Surname) < tblTours.Seats";
        DB.query(sql);
        break;
    }
}while (choice != 'Q');

DB.disconnect();
System.out.println("Done");
}
}
```

ANNEXURE H: SOLUTION – QUESTION 2: JAVA**OBJECT CLASS:**

```

import java.text.DecimalFormat;

/**
 *
 * Memo Question 2
 */
public class Quest2_MEMO {
    private String gName;
    private String dName;
    private String mName;
    private int numD;
    private int numT;
    private double tariff;

    public Quest2_MEMO(String gName, String dName, String mName, int numD, int
numT) {
        this.gName = gName;
        this.dName = dName;
        this.mName = mName;
        this.numD = numD;
        this.numT = numT;
        setTariff();
    }

    //=====
    private void setTariff()
    {
        String sName = mName.toUpperCase();
        //accept solution that doesn't use toUpperCase()
        if (sName.equals("DECEMBER") || sName.equals("APRIL") ||
sName.equals("SEPTEMBER"))
            tariff = 1250;
        else
            if (sName.equals("MAY") || sName.equals("MARCH") ||
sName.equals("JUNE") || sName.equals("JULY"))
                tariff = 900;
            else
                tariff = 1000;
    }

    //=====
    private String shortenString()
    {
        String shortname = mName.substring(0,1);
        String vowels = "AEIOU";
        //accept solution using lower case letters as well
        for (int cnt = 1; cnt < mName.length();cnt++)
        {
            char letter = mName.charAt(cnt);
            if(vowels.indexOf(mName.toUpperCase().charAt(cnt))<0)
            {
                shortname =shortname + letter;
            }
        }
        return shortname;
    }

    //=====
    public char findLuckyChar()
    {

```

```

    int last = dName.length()-1;
    int first = 1;
    int position = 0;
    boolean repeat = true;
    char charac = ' ';
    do
    {
        position = (int)(Math.random() * (last-first+1) + first);
        charac = dName.charAt(position);
        if (charac != ' ')
        {
            repeat = false;
            charac = dName.charAt(position);
        }
    }while (repeat == true);
    return charac;
}
//=====
public String toString()
{
    DecimalFormat df = new DecimalFormat("R 0.00");
    return "Month: " + shortenString() + "\nDestination: " + dName + " with
" + gName + " as the tour guide\nPrice: " + df.format(getTariff())+ " per day
for a period of " + numD + " days\n" + numT+ " tourists are taking this
tour\n";
}
//=====
public String getGName() {
    return gName;
}

public void setGName(String gName) {
    this.gName = gName;
}

public String getDName() {
    return dName;
}

public void setDName(String dName) {
    this.dName = dName;
}

public String getMName() {
    return mName;
}

public int getNumD() {
    return numD;
}

public void setNumD(int numD) {
    this.numD = numD;
}

public int getNumT() {
    return numT;
}

public void setNumT(int numT) {
    this.numT = numT;
}

```

```

    public double getTariff() {
        return tariff;
    }
}

```

APPLICATION/DRIVER CLASS:

```

import java.io.BufferedReader;
import java.io.InputStreamReader;
import java.io.FileReader;
import java.io.FileNotFoundException;

public class Question2_MEMO {

    public static void main(String[] args) throws Exception
    {
        Quest2_MEMO[] tourArray = new Quest2_MEMO[50];
        int counter = 0;
        BufferedReader kb = new BufferedReader(new InputStreamReader(System.in));
        // read from file
        try {
            BufferedReader bf = new BufferedReader(new FileReader("DataQ2.txt"));
            while (bf.readLine() != null)
            {
                counter++;
            }
            counter = counter/2;

            bf = new BufferedReader(new FileReader("DataQ2.txt"));
            for (int cnt = 0; cnt < counter; cnt++)

            {
                String line1 = bf.readLine();
                String line2 = bf.readLine();
                String[] temp1 = line1.split("&");
                String[] temp2 = line2.split(" for ");
                String[] temp3 = temp2[1].split(" days#");
                tourArray[cnt] = new Quest2_MEMO(temp1[0], temp1[1], temp2[0],
Integer.parseInt(temp3[0]), Integer.parseInt(temp3[1]));
            }
        }
        catch (FileNotFoundException e) {
            System.out.println(e);
            System.exit(0);
        }
        catch (Exception f) {
            System.out.println(f);
        }
        char choice = ' ';
        do {
            System.out.println("    MENU\n");
            System.out.println("Option A");
            System.out.println("");
            System.out.println("Q - QUIT");
            System.out.println("\nYour choice? ");

            choice = kb.readLine().toUpperCase().charAt(0);
            switch (choice) {
                case 'A':
                    System.out.print("Enter the month of tour(e.g. February): ");

```

```

String mnth = kb.readLine();

System.out.println("\n\nTours for the month of " + mnth);
System.out.println("=====\n");
System.out.println("Number          Destination\n");

for (int cnt = 0; cnt < counter - 1; cnt++) {
    if (tourArray[cnt].getMName().equalsIgnoreCase(mnth)) {
        System.out.println((cnt + 1)+ "\t\t"+ tourArray[cnt].getDName());
    }
}

System.out.print("\nEnter the number of a tour from the list e.g. 35:");
int num = Integer.parseInt(kb.readLine());
System.out.println("\n" + tourArray[num - 1]);
System.out.println("\nEnter any character from: " + tourArray[num -
1].getDName());

    char luckyC = kb.readLine().charAt(0);
    char genChar = tourArray[num - 1].findLuckyChar();
    if (luckyC == genChar) {
        System.out.println("Congratulations! You have received 25% discount on the
daily tariff! \nThe tariff was R " + (tourArray[num - 1].getTariff()) + " per
day. It has been reduced to R" + (tourArray[num - 1].getTariff() * 0.75) + "
per day\n\n");
    }
    else {
        System.out.println("The lucky character was the letter " + genChar + ".
\nNo discount. The tariff is still R " + tourArray[num - 1].getTariff() + " per
day\n\n");
    }
    break;
    case 'Q':
        System.out.println("Quit");
    }
} while (choice != 'Q');
}
}

```

ANNEXURE I: SOLUTION WITH OOP – QUESTION 3: JAVA

```
import java.io.BufferedReader;
import java.io.InputStreamReader;

// Object class to describe a tourist object

public class Tourist
{
    private String name;
    private String country;
    private String destination;
    private double money;
//=====
    public Tourist(String touristStr)
    {
        int atpos = touristStr.indexOf("@");
        int hashpos = touristStr.indexOf("#");
        name = touristStr.substring(0, atpos);

        country = touristStr.substring(atpos + 1,hashpos);
        String [] temp = touristStr.split("#");

        destination = temp[1];
        money = Double.parseDouble(temp[2]);
    }
//=====

    public void setDestination(String dest)
    {
        destination = dest;
    }

    public String getName()
    {
        return name;
    }

    public String getCountry()
    {
        return country;
    }

    public String getDestination()
    {
        return destination;
    }

    public double getMoney()
    {
        return money;
    }
}

// Class for the menu
import java.io.BufferedReader;
import java.io.InputStreamReader;
```

```

public class Question3_MEMO {

String[] arrData = {"Rachel Delarosa@Canada#SH#11861","Corradino
Grande@Spain#RO#5788",
"Lucas Herder@Germany#KR#7709", "Estotz Lizarazu@France#GA#12349",
"Chynna Taylor@England#GA#8551", "Renata Di@Spain#RO#4906",
"Ugs Boulot-Tolle@France#CA#7300", "Lena Bucholtz@Germany#GA#10344",
"Maria Heimpel@Germany#SH#9438", "Julian Amstadter@Germany#RO#8840",
"Sofie Mosbauer@Germany#GA#5894", "Fiona Green@England#CA#9094",
"Sara Escobedo@Canada#KR#4381", "Nataly Mahan@Canada#RO#12642",
"Wyatt Parham@Canada#SH#4799", "Noah Donovan@Canada#SH#3888",
"Joseph Scott@England#SH#7928", "Emily Smith@England#KR#3110",
"Adriana Mancuso@Spain#RO#3724", "Cassandra Wilder@Canada#KR#12583",
"Tomasino Camporese@Spain#KR#6777", "Stacy Anderson@England#RO#3686",
"Guiraud Bluteau@France#RO#11592", "Damian Friedman@Canada#RO#9012",
"Anne Loef@Germany#KR#13035", "Terence Brown@England#SH#8180",
"Lion Ghislieri@Spain#RO#14343", "Giraudetz Girardin@France#CA#11644",
"Guglielmo Capriati@Spain#SH#5408", "David Geiberger@Germany#RO#9854",
"Irisa Cooper@England#KR#11456", "Hayden Mcdonough@Canada#KR#7840",
"Jonas Hipp@Germany#RO#3137", "Emily Kohler@Germany#GA#6509",
"Emily Thul@Germany#RO#8551", "Gino Lazzaretti@Spain#CA#2329",
"Alex Hofstater@Germany#GA#6751", "Peers Scott@England#RO#9470",
"Liliana Horne@Canada#RO#14689", "Leon Kleinpaul@Germany#RO#15194"};

String []arrDestinations = {"Cape Winelands","Garden Route", "Kruger National
Park", "Robben Island (English tour)","Robben Island (Other tour)",
"Shakaland"};

    BufferedReader kb;

//=====
    public void runMenu() throws Exception {

        kb = new BufferedReader(new InputStreamReader(System.in));
        char choice = ' ';
        do {
            System.out.println("MENU");
            System.out.println();
            System.out.println("    Option A");
            System.out.println("    Option B");
            System.out.println("    Option C");

            System.out.println();
            System.out.println("Q - QUIT");
            System.out.println();
            System.out.println("Your choice?");
            choice = kb.readLine().toUpperCase().charAt(0);
            switch (choice) {
                case 'A': convertEuros();
                    break;
                case 'B': divideGroup();
                    break;
                case 'C': determinePopularity();
                    break;
                case 'Q':
                    System.out.println("QUIT");
            }
        } while (choice != 'Q');
    }
}

```



```

    }

//=====
//Option A
    public void convertEuros()
    {
        double value = 0;
        for (int c = 0; c < arrData.length; c++)
        {
            Tourist tourist = new Tourist(arrData[c]);
            String country = tourist.getCountry();
            if (country.equalsIgnoreCase("France")
||country.equalsIgnoreCase("Spain") || country.equalsIgnoreCase("Germany"))
            {
                value = value + tourist.getMoney();
            }
        } //for
        System.out.printf("%s%-8.0f\n", "Total amount in euro: ", value);
        double rand = value*10.75;
        System.out.printf("%sR%10.2f\n\n", "Total amount in South African rand: ",
            rand);
    }

//=====
// Option B
    public void divideGroup()
    {
        System.out.println("List of English-speaking tourists to Robben
Island");

        System.out.println("=====");
        for (int c = 0; c < arrData.length; c++)
        {
            Tourist tourist = new Tourist(arrData[c]);
            String dest = tourist.getDestination();

            if (dest.equals("RO"))
            {
                String country = tourist.getCountry();
                if (country.equalsIgnoreCase("England") ||
country.equalsIgnoreCase("Canada"))
                {
                    System.out.println(tourist.getName());
                    arrData[c] = arrData[c].replace("#RO#", "#ROEnglish#");
                    tourist.setDestination("ROEnglish");
                }
                else
                {
                    arrData[c] = arrData[c].replace("#RO#", "#ROOther#");
                    tourist.setDestination("ROOther");
                } // else
            } // if
        } // for

        System.out.println("\n\n");
    }

//=====
// Option C
    public void determinePopularity()
    {

```

```

        int[] arrCount = new int[6];
        System.out.println("Star rating of tours");
        System.out.println("=====");
        System.out.println("Destination          Rating      Number of
tourists");
        System.out.println("=====");
        for (int c = 0; c < 6; c++)
        {
            arrCount[c]=0;
        }
        for (int c = 0; c < arrData.length; c++)
        {
            Tourist tourist = new Tourist(arrData[c]);
            String destcode = tourist.getDestination();
            switch (destcode.toUpperCase().charAt(0))
            {
                case 'C' : arrCount[0]++; break;
                case 'K' : arrCount[2]++; break;
                case 'G' : arrCount[1]++; break;
                case 'R' : if (destcode.toUpperCase().charAt(2) == 'E')
                    arrCount[3]++;
                    else arrCount[4]++;break;
                case 'S' : arrCount[5]++;break;
            }
        }
        // for
        // output
        for (int i = 0; i < 6; i++)
        {
            String starString = "";
            int numStars = arrCount[i]/3;
            for (int s = 0; s < numStars; s++)
            {
                starString = starString + "*";
            }
            String outString = String.format("%-35s%-
10s(%d)",arrDestinations[i],starString,arrCount[i]);
            System.out.println(outString);
        }

        System.out.println("\n\n");
    }
}
//=====
// Test class creating an object of the menu class

import java.io.IOException;

public class TestQuestion3_Memo
{
    public static void main(String[] args) throws Exception {

        Question3_MEMO Q3 = new Question3_MEMO();
        Q3.runMenu();
    }
}

```

ANNEXURE J: SOLUTION WITHOUT OOP – QUESTION 3: JAVA

```

import java.io.BufferedReader;
import java.io.InputStreamReader;

public class Question3_MEMO {

String[] arrData = {"Rachel Delarosa@Canada#SH#11861", "Corradino
Grande@Spain#RO#5788",
"Lucas Herder@Germany#KR#7709", "Estotz Lizarazu@France#GA#12349",
"Chynna Taylor@England#GA#8551", "Renata Di@Spain#RO#4906",
"Ugs Boulot-Tolle@France#CA#7300", "Lena Bucholtz@Germany#GA#10344",
"Maria Heimpel@Germany#SH#9438", "Julian Amstadter@Germany#RO#8840",
"Sofie Mosbauer@Germany#GA#5894", "Fiona Green@England#CA#9094",
"Sara Escobedo@Canada#KR#4381", "Nataly Mahan@Canada#RO#12642",
"Wyatt Parham@Canada#SH#4799", "Noah Donovan@Canada#SH#3888",
"Joseph Scott@England#SH#7928", "Emily Smith@England#KR#3110",
"Adriana Mancuso@Spain#RO#3724", "Cassandra Wilder@Canada#KR#12583",
"Tomasino Camporese@Spain#KR#6777", "Stacy Anderson@England#RO#3686",
"Guiraud Bluteau@France#RO#11592", "Damian Friedman@Canada#RO#9012",
"Anne Loef@Germany#KR#13035", "Terence Brown@England#SH#8180",
"Lion Ghislieri@Spain#RO#14343", "Giraudetz Girardin@France#CA#11644",
"Guglielmo Capriati@Spain#SH#5408", "David Geiberger@Germany#RO#9854",
"Irisa Cooper@England#KR#11456", "Hayden Mcdonough@Canada#KR#7840",
"Jonas Hipp@Germany#RO#3137", "Emily Kohler@Germany#GA#6509",
"Emily Thul@Germany#RO#8551", "Gino Lazzaretti@Spain#CA#2329",
"Alex Hofstater@Germany#GA#6751", "Peers Scott@England#RO#9470",
"Liliana Horne@Canada#RO#14689", "Leon Kleinpaul@Germany#RO#15194"};

String []arrDestinations = {"Cape Winelands", "Garden Route", "Kruger National
Park", "Robben Island (English tour)", "Robben Island (Other tour)",
"Shakaland"};

    BufferedReader kb;
//=====
//Option A
    public void convertEuros()
    {
        double value = 0;
        for (int cnt = 0; cnt < arrData.length; cnt++)
        {
            if (arrData[cnt].indexOf("France")>=0
||arrData[cnt].indexOf("Spain")>=0||arrData[cnt].indexOf("Germany")>=0)
            {
                String[] temp = arrData[cnt].split("#");
                value = value + Double.parseDouble(temp[2]);
            }
        }
        System.out.printf("%s%-8.0f\n", "Total amount in euro: ", value);
        double rand = value*10.75;
        System.out.printf("%sR%10.2f\n\n", "Total amount in South African rand: ",
rand);
    }
//=====
//Option B
    public void divideGroup()
    {
        System.out.println("List of English-speaking tourists to Robben Island");

        System.out.println("=====");
        for (int cnt = 0; cnt < arrData.length; cnt++)

```

```

{
  if (arrData[cnt].indexOf("#RO#") >= 0)
  {
    if (arrData[cnt].indexOf("England")>=0 ||arrData[cnt].indexOf("Canada") >= 0)
    {
      String[] temp = arrData[cnt].split("@");
      System.out.println(temp[0]);
      arrData[cnt] = arrData[cnt].replace("#RO#", "#ROEnglish#");
    }
  }
  else
  {
    arrData[cnt] = arrData[cnt].replace("#RO#", "#ROOther#");
  }
}
}
System.out.println("\n\n");
}

//=====
// Option C
public void determinePopularity()
{
  int[] arrCount = new int[6];
  System.out.println("Star rating of tours");

System.out.println("=====");
System.out.println("Destination                Rating      Number of
tourists");

System.out.println("=====");
for (int c = 0; c < 6; c++)
{
  arrCount[c]=0;
}

for (int c = 0; c < arrData.length; c++)
{
  int endpos = arrData[c].indexOf("#");
  String destcode = arrData[c].substring(endpos + 1,endpos + 4);
  switch (destcode.toUpperCase().charAt(0))
  {
    case 'C' : arrCount[0]++; break;
    case 'K' : arrCount[2]++; break;
    case 'G' : arrCount[1]++; break;
    case 'R' : if (destcode.toUpperCase().charAt(2) == 'E')
                arrCount[3]++;
                else arrCount[4]++;break;
    case 'S' : arrCount[5]++;break;
  }
}
} // for
// output
for (int index = 0; index < 6; index++)
{
  String starString = "";
  int numStars = arrCount[index]/3;
  for (int stars = 0; stars < numStars; stars++)
  {
    starString = starString + "*";
  }
  String outString = String.format("%-35s%-
10s(%d)",arrDestinations[index],starString,arrCount[index]);
  System.out.println(outString);
}

```

```
    }
    System.out.println("\n\n");
}
public Question3_MEMO() throws Exception {
    kb = new BufferedReader(new InputStreamReader(System.in));
    char choice = ' ';

do {
    System.out.println("MENU");
    System.out.println();
    System.out.println("    Option A");

    System.out.println("    Option B");
    System.out.println("    Option C");
    System.out.println();
    System.out.println("Q - QUIT");
    System.out.println();
    System.out.println("Your choice?");
    choice = kb.readLine().toUpperCase().charAt(0);
    switch (choice) {
    case 'A': convertEuros();
              break;
    case 'B': divideGroup();
              break;
    case 'C': determinePopularity();
              break;
    case 'Q':
              System.out.println("QUIT");
    }
} while (choice != 'Q');
}

public static void main(String[] args) throws Exception {
    new Question3_MEMO();
}
}
```